



FRANGIZOLLE X



ROSSETTO

TECNOLOGIA IN LAVORO



FRANGIZOLLE "X"



**"DA UNA
BUONA BASE...
OTTIMI FRUTTI!"**



Il FRANGIZOLLE X è la macchina combinata che garantisce velocità operativa e risparmio in termini di tempo e carburante.

IDEALE PER:

- Minima lavorazione;
- Rottura estiva delle stoppie;
- Preparazione del letto di semina per cereali autunno-vernini;
- Lavorazioni interfileari in frutteti e vigneti;
- Rovesciamento senza inversione del terreno;
- Lavorazione a doppio strato su sodo o arato;
- Affinamento del terreno.

CONFIGURAZIONE DI SERIE:

- Fila anteriore di dischi bombati e dentati/lisci d. 610/660 x 6 regolabile nell'inclinazione;
- Coltivatore ad ancora rigide regolabili in altezza, con protezione e sistema di sganciamento mediante viti di sicurezza ad alto carico di rottura, disposte su due file a profondità variabile meccanica o idraulica;
- Fila posteriore di dischi bombati e dentati/lisci d. 610/660 x 6 o ondulati d. 560 x 6, regolabile nell'inclinazione;
- Ripiegamento idraulico in verticale delle dischiere;
- Supporti oscillanti a doppio cuscinetto con protezione antiusura che, grazie alla solida costruzione, garantiscono la massima tenuta e durata;
- Albero dischiere in acciaio quadro 40;
- Ruota posteriore idraulica.

Disk harrow is the combined machine that guarantees high operating speed and saving time and fuel.

IT IS IDEAL FOR:

- Minimum tillage;
- Summer break stubbles;
- Seed-bed preparation for autumn-winter cereals;
- Working between rows in orchards and vineyards;
- Soil turning without remixing tilled layers;
- Double layer working on compact or ploughed ground;
- Soil refinement.

SERIES CONFIGURATION:

- Front row rounded and toothed/plain discs d. 610/660 x 6 adjustable in the inclination;
- Cultivator with rigid anchors registered in the height, with protection and a release system through steel security screws at high charge of breaking, placed on two rows at mechanics or hydraulic variable depth;
- Back row rounded and toothed/plain discs d. 610/660 x 6 or waved discs d. 560 x 6, adjustable in the inclination;
- Hydraulic folding in vertical of disk;
- Floating supports at double bearings with anti-wear protection that, thanks to the strong construction, guarantee the maximum seal and duration;
- Disk shaft in steel, board 40;
- Hydraulic back wheel.

TIPO/TYPE	HP	N° Dischi Discs no.	N° Supporti Supports no.	Largh. m. Width m.
FRG/28	130/150	20	8	2,80*
FRG/32	150/180	24	8	3,20*
FRG/38	180/200	28	12	3,80*
FRG/43	200/250	32	12	4,30*

* Chiusura idraulica a m. 2,50 - * Hydraulic folding m. 2,50



ROSSETTO
di Rossetto Gian Paolo e C. Snc
37046 MINERBE (Verona) Italy
Tel. 0442 640185 - Fax 0442 640711
www.rossettoffli.it - info@rossettoffli.it